

SF6381X

Product Family: Oven Category: 60cm

Power supply: Electric Heat source: Electric

Cooking method: Fan assisted Oven control: Electro-mechanical

EAN code: 8017709195762



Aesthetics

Aesthetics: Classic Design: Flat

Colour: Fingerproof Stainless Steel

Material: Stainless steel Type of steel: Brushed Glass Type: Eclipse Serigraphy colour: Black Serigraphy type: Symbols Door: With 2 horizontal strips

Handle: Classic

Handle Colour: Steel effect

Logo: Embossed

Programs / Functions

No. of cooking functions: 6
Traditional cooking functions















Controls

Control setting: Control knobs

No. of controls: 3 Control knobs: Classic Controls colour: Steel effect



Options

Timer: Electro-mechanical

Time-setting options: Automatic end cooking

Minute minder

End of cooking acoustic alarm

Technical Features

Temperature control: Electro-mechanical

Minimum Temperature: 50 °C Maximum temperature: 250 °C Cavity material: Ever clean Enamel

No. of shelves: 5

Shelves type: Metal racks

N. of fans: 1 No. of lights: 1 Light type: Halogen Light Power: 40 W

Lower heating element power: 1200 W Upper heating element - Power: 1000 W

Grill element - power: 1700 W Large grill - Power: 2700 W Door: Temperate door Removable door Full glass inner door Removable inner door Total no. of door glasses: 3

No. of thermoreflecting door glasses: 2

Safety Thermostat

Cooling system: Tangential Cooling duct: Single

Usable cavity space dimensions (HxWxD): 360x460x425 mm

Performance / Energy Label

Energy efficiency class (2002/40/CE): A

Energy efficiency class: A

Net volume of the cavity: 70 litres

Energy consumption per cycle in conventional mode: 1.15 KWh Energy consumption per cycle in fan-forced convection: 0.8

KWh

Energy efficiency index: 95.2 %

No. of cavities: 1 Gross volume: 79 litres

Accessories Included

Grid with back stop: 1

Enamelled deep tray (40mm): 1

Electrical Connection

Voltage: 220-240 V

Electrical connection rating (W): 3000 W

Current: 13 Amp

Frequency (Hz): 50/60 Hz

Power supply cable length: 115 cm

Accessories not included



BN620-1

Enamelled tray, 20mm deep



BN640

Enamelled tray, 40mm deep



BNP608T

Teflon tray, 8mm deep



BVG

Glass tray and stainless steel grid, 40mm deep





GT1P-2

Partially extractable telescopic guides (1 level) for ovens with metal frames. Length: 355.5 mm, extraction: 285 mm. Material: Stainless steel AISI 430 polished.



GT1T-2

Totally extractable telescopic guides (1 level) for ovens with metal frames. Length: 355.5 mm, extraction: 418.5 mm. Material: Stainless steel AISI 430 polished.



MDR

Handle for double tray



PALPZ

Pizza shovel with fold away handle width: 315mm length: 325mm



PC681-1

Set of catalytic panels, 5 levels, 1 lamp



PIR2

Steel pan with grid, glass top, not suitable for ovens with telescopic guides



PPR₂

Refractary pizza stone without handles. Squared shaped stone: L42 x H1,8 x D37,5 cm. Suitable also for gas ovens, to be put on the griddle.



PR3845X

Antifingerprint stainless steel. Cover for furniture in column installation of more ovens



PRTX

Refractary pizza stone with handles. D=35cm Not suitable for microwave ovens. Suitable for gas ovens, to be put on the griddle.



SFLK

Child lock



SFLK1

Child lock



